



www.its-africa.co.za

Simply Clean



KÄRCHER HIGH PRESSURE CLEANERS

Description

The main benefit of the new "Upright"-class class of hot water high-pressure cleaners is the horizontal machine concept. This ensures low weight, compact dimensions and the ease with which they can be loaded and transported. They fit also easily in vertical position in a station wagon for transportation from one location to the next.

Thanks to their compact size, these units take up a minimum of storage space when they are not in use.

Large diameter wheels as well as a ergonomically shaped push/pull handle ensure excellent manoeuvrability and mobility, even on difficult surfaces.

KÄRCHER HDS 5.11 UX

LIST PRICE : R 24 300.00

OUR PRICE : R 15 300.00

YOU SAVE : R 9 000.00

*Price excludes vat.



KÄRCHER HDS5.11 UX HOT WATER HIGH PRESSURE CLEANER

The three-piston axial high-pressure pump has hardened stainless-steel pistons and a brass cylinder head. A pressure switch shuts down the unit automatically when the trigger gun is closed. This relieves the load on components and prolongs their service lives.

High-pressure pump, burner fan and heating oil pump are driven by an electric motor and are combined to form a drive module. This principle not only ensures a very compact assembly and a high power output, it also makes the units exceptionally reliable.

The characteristics of the time-proven Kärcher boiler-technology are high performance in a minimum of space while ensuring full compliance with the statutory emission limits.

Single-phase unit with air-cooled two-pole electric motor. Three-piston axial pump with hardened stainless-steel pistons. Chemical feed in low-pressure mode.

Application

- Cleaning vehicles and workshops in small companies, such as
- locksmith
- Plumbers, gas-/ heating installers
- Painters, floor tilers and plasterer with occasional facade cleaning work
- General cleaning tasks in the crafts and trades
- small garages, tire dealers
- Building service contractors

Features & Benefits

Central control panel
One-switch-control for on/off and hot and cold water operation.

Plastic chassis with integrated 6,5 l fuel tank .Multifunctional, corrosion-proof, impact-resistant and shock-proof Chassis with bumper and integrated hose and accessory storage.

Flue gas temperature monitoring .The flue gas temperature limiter installed in the outlet switches off the drive motor if the flue gas temperature exceeds over max. temperature and thus ensures additional operator safety.

Efficiency: With a max. water temperature of 80°C the machine cleans also stubborn oily and greasy stains. Fine mesh water filter

Standard accessories

- Trigger gun, extended
- High-pressure hose, 15 m
- Spray lance, 550 mm
- Integral high-pressure hose reel
- Anti-twist system (AVS)
- Pressure switch control

Technical data:

Power supply	1 / 230 / 50 Ph/V/Hz
Water flow rate	450 l/h
Operating pressure	110 / 11 bar/MPa
Max. pressure	190 bar
Max. water feed temperature	max. 80°C
Weight	70 kg
Dimensions (L x W x H)	620 x 620 x 1160 mm

R15 300.00 SPECIAL VAT



National Premium Dealership



0861 ASK ITS 275 487
CALL US NOW
customer@its-africa.co.za

Johannesburg Office : Number 6 Arklow Road, Founders View South
 Cape Town Office : 23 Palmiet Street, Kaymor Industria, Stikland
 Port Elizabeth Office : 17 Uitenhage road, Sydenham,
 George Office : Cnr Albert and Nywerheid Street, George Industrial

Tel: 011 524 0886 Fax: 011 524 0887
 Tel: 021 949 7665 Fax: 021 949 5813
 Tel: 041 484 2919 Fax: 041 487 0082
 Tel: 044 873 6040 Fax: 044 873 6040